

Strong supremacy of quantum systems as communication resource

Maria Quadeer and Manik Banik

*Optics & Quantum Information Group, The Institute of Mathematical Sciences,
HBNI, C.I.T Campus, Tharamani, Chennai 600 113, India.*

Andris Ambainis and Ashutosh Rai

*Center for Quantum Computer Science, Faculty of Computing,
University of Latvia, Raina bulv. 19, Riga, LV-1586, Latvia.*

We investigate the task of d -level random access codes (d -RACs) and consider the possibility of encoding classical strings of d -level symbols (dits) into a quantum system of dimension d' strictly less than d . We show that the average success probability of recovering one (randomly chosen) dit from the encoded string can be larger than that obtained in the best classical protocol for the task. Our result is intriguing as we know from Holevo's theorem (and more recently from Frenkel-Weiner's result [Commun. Math. Phys. 340, 563 (2015)]) that there exist communication scenarios wherein quantum resources prove to be of no advantage over classical resources. A distinguishing feature of our protocol is that it establishes a stronger quantum advantage in contrast to the existing quantum d -RACs where d -level quantum systems are shown to be advantageous over their classical d -level counterparts.

PACS numbers: 03.65.Ud, 02.50.Le, 03.67.Ac

I. INTRODUCTION

Information theory fundamentally deals with the problem of reproducing at one point, either exactly or approximately, a message selected at another point. The mathematical model for classical information theory was founded in a seminal paper by Claude Shannon in the year 1948 [1]. In the last few decades, application of quantum theory to information processing tasks has lead to several discoveries [2–6] and their synthesis has given birth to the epoch of quantum information theory [7, 8]. Suitable use of resources from quantum theory can outperform their classical counterparts in several information theoretic, communication, and computational tasks and some of these proposals have already been implemented by the present day quantum technologies [9, 10].

The advantage of quantum mechanical systems over classical systems may be ascribed to the fact that the state of a quantum system is given by a unit vector in some complex vector space. However, some information processing tasks in quantum theory are restricted. For example, the Holevo's theorem [11] puts a restriction on the amount of classical information that can be extracted from a quantum state (*accessible information*). More recently, a remarkable theorem due Frenkel and Weiner [12] shows that the classical information storage in a d -Level quantum system can not be more than the corresponding d -state classical system. Despite of such restrictions, a quantum system can give advantage in a suitably designed communication task known as *Random Access Codes* (RACs). These were initially introduced by Weisner by the name of conjugate coding

[13], and was later rediscovered in [14, 15] by Ambainis *et al.* As pointed out in [15], the possibility of encoding infinite amount of classical information in a single quantum state (a vector in a complex Hilbert space) and the freedom to perform different non-commutative measurements for extracting the encoded information render quantum random access codes (QRACs) advantageous. QRACs establish that Bennett's first law of quantum information, i.e., "1 qubit $\geq$ 1 bit" [16] (here $X \geq Y$ reads as "X can do the job of Y") is actually strict, i.e., as a communication resource 1 qubit outperforms 1 bit in RAC tasks. Recently, Tavakoli *et al.* have studied RACs with high-level symbols that use d -level classical and quantum systems [17]. It has been proved that high-level quantum systems provide significant advantage in the average performances of the RAC tasks over their classical counterparts [17, 18]. In other words, generalized version of Bennett's first law, that "1 qudit $\geq$ 1 dit" is also strict, i.e., in a d -level RAC quantum system outperforms its classical counterpart.

Here, we ask whether a d' -level quantum system can outperform a d -level classical system in some communication task, where $d' < d$. Interestingly, we find that the answer is in the affirmative. We show that for high-level RACs there exist quantum codes that use relatively lower-level quantum systems for encoding to give better average success probability compared to the best classical codes that use high-level classical systems for encoding. This establishes an advantage of lower level quantum systems as communication resources over a higher level classical system. It is important to note that the quantum supremacy established by our protocol is stronger than that established in the existing QRAC

protocols. In other words, we can say that in certain communication tasks $1 \text{ qu-}d'\text{-dit} \succ 1 \text{ } d\text{-dit}$ with $d' < d$.

The paper is organized as follows: We briefly review RACs in section-II; in section-III, we discuss the high-level RACs; in section-IV, we present our protocol for implementing high-level RACs with lower-level quantum systems, and finally give our conclusions in section-V.

II. RANDOM ACCESS CODES: A QUICK OVERVIEW

Random access codes (RACs) are a class of communication tasks involving two separated parties, (say) Alice and Bob. Alice is given an n -bit string $x = x_1 \dots x_n$ chosen uniformly at random from the set $\{0, 1\}^n$. The other party, Bob is given a number $y \in \{1, \dots, n\}$, chosen uniformly at random. Bob's task is to correctly guess the y^{th} bit of Alice. Alice can help Bob in guessing the bit by sending some information about her string. However, the amount of information that Alice can send to Bob is restricted to 1-cbit. We denote such a RAC by the symbol $[n \xrightarrow{p} 1]$, meaning that n bits are encoded into 1 bit and p denotes the merit of the success of recovering initial bits which can be either 'average success probability' (P_a) or 'worst case success probability' (P_w). In the quantum version of RAC, Alice can encode her n -bit string into a two level quantum system, i.e., a qubit. One can also define a more general version of RAC denoted by $[n \xrightarrow{p} m]$ (with $m \leq n$), which is defined analogous to the $[n \xrightarrow{p} 1]$ RACs [14, 15, 19]. Throughout this paper we consider RACs with $m = 1$.

For the simplest $2 \xrightarrow{p} 1$ RAC, the worst case classical success probability is $P_w^C = 1/2$ and the corresponding optimal classical average success probability is $P_a^C = 3/4$. Here we use the upper-index 'C' to denote the classical case. If Alice sends one of the bit in her string (either first or second bit), Bob can guess that bit correctly but he has to guess the other bit randomly. This naive protocol gives the aforementioned optimal classical success probability (both worst and average), and moreover one can show that no other classical protocol can do better [18]. Interestingly, the authors in [14, 15] have shown that for such a classical RAC non-trivial quantum protocols exist which is described as the following : Alice can encode her string $x_1 x_2$ into the state $|\psi\rangle \in \mathbb{C}^2$ of a two-level quantum system using the following encoding scheme :

$$x_1 x_2 \rightarrow |\psi_{x_1 x_2}\rangle := \sigma_X^{x_1} \sigma_Z^{x_2} |\psi_{00}\rangle,$$

where σ_X, σ_Z are Pauli operators and $|\psi_{00}\rangle := (|0\rangle + |0_X\rangle)/\sqrt{2 + \sqrt{2}}$, with $|0\rangle$ ($|0_X\rangle$) being the 'up' eigenstate of Pauli-Z (Pauli-X) operator. To decode the first bit, Bob, after receiving the encoded particle from Alice, performs a σ_Z measurement (i.e performs measurement

in computational basis $\{|0\rangle, |1\rangle\}$) on it and guesses the bit value to be 0 (1) upon obtaining the 'up' ('down') outcome. For the second bit, Bob performs σ_X measurement and similarly guesses the outcome. For this encoding-decoding scheme, the worst case success probability is $P_w^Q = \frac{1}{2} \left(1 + \frac{1}{\sqrt{2}}\right) > \frac{1}{2} = P_w^C$. It is easy to see that the average success probability is the same as that of the worst case, thus $P_a^Q = \frac{1}{2} \left(1 + \frac{1}{\sqrt{2}}\right) > P_a^C$. Later, Chuang (as mentioned in [15]) generalized this protocol to a $3 \xrightarrow{0.78} 1$ QRAC, while Hayashi *et al.* [20] proved that no quantum $n \xrightarrow{p} 1$ RAC exists for $n \geq 4$ with $p_w > 1/2$. However, it has been shown that $n \xrightarrow{p} 1$ QRAC is possible for any $n \geq 1$ with $p_w > 1/2$ provided that shared randomness is accessible to both parties [21].

At this point we would like to mention that QRACs have been originally studied in the context of quantum finite automata [14, 15]. They also have applications in quantum communication complexity [22–24], in particular for network coding [25] and locally decodable codes [26, 27]. QRACs have also been applied to the quantum state learning problem [28]. In recent times, this study also finds applications in semi-device-independent random number expansion [29] as well as semi-device-independent key distribution [30]. Also, the study of QRACs and it's variant, namely *parity oblivious* RACs has foundational implications [31–33], in particular they have been studied for operational depiction of preparation contextuality of mixed quantum states.

III. HIGH-LEVEL RANDOM ACCESS CODES

Recently Tavakoli *et al.* have studied high-level RACs in Ref.[17]. Alice receives an n -dit string $x = x_1, \dots, x_n$, uniformly at random, where a *dit* i.e x_i takes values from an alphabet set $\{0, 1, \dots, d-1\}$. She then encodes her string x into a classical d -level system (or a quantum d -level system), which she can send to Bob in any state she wishes. Bob receives a number $y \in \{1, \dots, n\}$ chosen uniformly at random and his task is to recover the y^{th} dit, i.e., x_y of Alice's string. Such a task is denoted by $[(n, d) \rightarrow 1]$ RAC. As conjectured in [17] and later proved in [18], the maximum average success probability for classical RACs is achieved by the 'majority-encoding identity-decoding' protocol. A closed analytical formula for the classical average success probability in this task is hard to derive for general values of parameters n and d . However, for $[(2, d) \rightarrow 1]$ and $[(3, d) \rightarrow 1]$ cases, the analytic expressions can be obtained for the maximum success probabilities, that read $P_a^C(2, d) = \frac{1}{2}(1 + \frac{1}{d})$ and $P_a^C(3, d) = \frac{1}{3}(1 + \frac{3}{d} - \frac{1}{d^2})$ respectively. The authors in [17] have also constructed non-trivial quantum protocols for $[(2, d) \rightarrow 1]$ and $[(3, d) \rightarrow 1]$ cases. The

$[(2, d) \rightarrow 1]$ quantum protocol is a generalized version of the $[(2, 2) \rightarrow 1]$ protocol already discussed in the previous section. We describe the protocol here for completeness: Consider the computational basis $\mathbb{B}_C := \{|l\rangle\}_{l=0}^{d-1}$ in the Hilbert space $\mathbb{C}^d$ and also consider the Fourier basis $\mathbb{B}_F := \{|e_l\rangle = \frac{1}{\sqrt{d}} \sum_{k=0}^{d-1} \omega^{kl} |k\rangle\}_{l=0}^{d-1}$, with ω being the d^{th} root of unity, i.e., $\omega = \exp(\frac{2\pi i}{d})$. Consider the operators $X = \sum_{k=0}^{d-1} |k+1\rangle\langle k|$ and $Z = \sum_{k=0}^{d-1} \omega^k |k\rangle\langle k|$. Alice encodes her strings in the following manner:

$$x_1 x_2 \rightarrow |\psi_{x_1 x_2}\rangle = X^{x_1} Z^{x_2} |\psi_{00}\rangle, \quad (1)$$

where $|\psi_{00}\rangle = \frac{1}{\sqrt{2}}(|0\rangle + |e_0\rangle)$, with $N_{2,d} = \sqrt{2 + 2/\sqrt{d}}$ being the normalization constant. For decoding the first dit x_1 Bob performs a measurement in the computational basis $\mathbb{B}_C$ and guesses the value as l when the projector $|l\rangle\langle l|$ clicks in the measurement. Similarly, for the second dit, he performs a measurement in the Fourier basis $\mathbb{B}_F$ and guess the dit value according to the measurement outcome. This protocol gives average success probability $P_a^Q(2, d) = \frac{1}{2}(1 + \frac{1}{\sqrt{d}})$ which is strictly greater than the corresponding optimal classical success probability $P_a^C(2, d) = \frac{1}{2}(1 + \frac{1}{d})$ for all d . As pointed out in [17], the optimal advantage of the QRAC over the RAC measured by the ratio of the success probabilities is observed for $d = 6$.

IV. HIGH-LEVEL RAC WITH LOWER-LEVEL QUANTUM ENCODING

We consider the $[(2, d) \rightarrow 1]$ RAC task, but Alice has access to a d' -dimensional quantum system to encode her classical message where the dimension d' of the quantum system is strictly less than d . We investigate whether with a limited dimensional quantum system Alice and Bob can construct non-trivial quantum codes for the task. It turns out that the following QRAC protocol has this interesting feature.

Alice's encoding: Alice encodes her string $x_1 x_2 \in \{0, 1, \dots, d-1\}^2$ as follows:

$$x_1 x_2 \rightarrow |\psi_{x_1 x_2}\rangle := \mathcal{G}(x_1, x_2, X, Z) |\psi_{00}\rangle \in \mathbb{C}^{d'} \quad (2)$$

with $|\psi_{00}\rangle$ being the normalized state considered in Eq.(1), and

$$\mathcal{G}(x_1, x_2, X, Z) = \begin{cases} X^{x_1} Z^{x_2}, & \text{if both } x_1, x_2 \leq d' \\ \mathbb{1}, & \text{otherwise.} \end{cases}$$

with X, Z being the operators as defined in the previous section, and $\mathbb{1}$ is the identity operator.

Bob's decoding: To decode the first dit Bob performs measurement in the computational basis $\{|l\rangle\}_{l=0}^{d'-1}$ and on obtaining outcome $l \in \{1, \dots, d' - 1\}$ he guesses the




Figure 1. (Color online) : Plot r vs d . The plot (red dots) gives the *dimensional advantage* $r = d - d'$ of the quantum system used for encoding as a function of d . The minimum value of d for which a restricted quantum encoding is advantageous over the best classical d -RAC is $d = 6$. This advantage in general increases with increasing d although remains flat in some range of d . For example, $r = 1$ for $d \in \{6, \dots, 11\}$ and then increases to $r = 2$ for $d \in \{12, \dots, 19\}$, etc.

value as l , but when he obtains the outcome $l = 0$ he guesses an answer from the set $\{0, d', d' + 1, \dots, d - 1\}$ uniformly at random. To guess the value of the second dit, he performs a measurement in the Fourier basis $\{|e_l\rangle = \frac{1}{\sqrt{d}} \sum_{k=0}^{d'-1} \omega^{kl} |k\rangle\}_{l=0}^{d'-1}$ and uses the same strategy as before to make a guess. The average success probability of this quantum protocol turns out to be:

$$P_{res}^Q = \frac{d - r}{2d} \left[1 + \frac{1}{\sqrt{d - r}} \right], \quad (3)$$

where we call $r = d - d'$ a *dimensional advantage* since it gives the extent to which one can lower the dimension of the quantum system used for encoding and still get advantage over the best classical protocol. For any classical $[(2, d) \rightarrow 1]$ RAC the optimal average success probability is $P_a^C(2, d) = \frac{1}{2}(1 + \frac{1}{d})$. Therefore, in order to do better, our quantum protocol must satisfy

$$P_{res}^Q > P_a^C(2, d) \implies d > r^2 + 3r + 1. \quad (4)$$

Condition-(4) implies that our quantum protocol gives advantage for $d \geq 6$ and $r \in \{1, \dots, \lfloor \frac{1}{2}(-3 + \sqrt{4d + 5}) \rfloor\}$, where $\lfloor a \rfloor$ is the greatest integer less than or equal to a . This means that the smallest value of d' that yields an advantage is restricted. For small values of d , the allowed value of d' is exactly $d - 1$, as dictated by condition-(4) (See Fig.1). As d increases, the allowed values of d' become $d - 1$ and $d - 2$ and so on. Therefore, one cannot arbitrarily choose

any lower d' dimensional quantum system to supersede the optimal classical d -RAC protocol. In fact, there exists a minimum value of d' , encoding below which would be bad, since it would yield a success probability lower than that of the optimal classical d -RAC. Fig. 1 illustrates how the dimensional advantage $r = d - d'$ grows with d . Note that for $d = \{2, 3, 4, 5\}$ we get no dimensional advantage (In Fig. 1, $r = 0$ corresponds to this case).

V. CONCLUDING REMARKS

In conclusion, our protocol demonstrates the supremacy of a lower-dimensional quantum system over its higher-dimensional classical counterpart, a consequence of the existence of superposition of states and non-commutative measurements in quantum theory. Our result is slightly stronger than the earlier results on RACs which prove the advantage of using a quantum system over a classical system of the same dimension [17]. In general, the study of QRACs is important as there exist communication scenarios where the use of quantum resources proves to be of no advantage over

their classical counterparts, a result of Holevo's theorem [11], a general version of which has been proved more recently by Frenkel and Weiner [12]. While these theorems address the question of encoding and decoding a random variable, RACs are concerned with decoding randomly chosen parts of such an encoded random variable. Finally, we would like to state that proving the optimality of high-level RACs using a limited dimensional quantum system remains an open problem and needs further investigation.

ACKNOWLEDGMENTS

MB and AR would like to thank Prof. G. Kar for his comments and suggestions. MB acknowledges his visit at the University of Latvia where a part of the work was done. MQ acknowledges her visit at the Institute of Mathematical Sciences, Chennai. AR and AA acknowledge support by the European Union Seventh Framework Programme (FP7/2007-2013) under the RAQUEL (Grant Agreement No. 323970) project, QALGO (Grant Agreement No. 600700) project, and the ERC Advanced Grant MQC.

-
- [1] C. E. Shannon, A Mathematical Theory of Communication, *The Bell System Technical Journal* **27**, 379–423; 623–656 (1948).
 - [2] C. H. Bennett and S. J. Wiesner, Communication via one- and two-particle operators on Einstein-Podolsky-Rosen states, *Phys. Rev. Lett.* **69**, 2881 (1992).
 - [3] C. H. Bennett, G. Brassard, C. Crepeau, R. Jozsa, A. Peres, and W. K. Wootters, Teleporting an Unknown Quantum State via Dual Classical and Einstein-Podolsky-Rosen Channels, *Phys. Rev. Lett.* **70**, 1895 (1993).
 - [4] L. Grover, A fast quantum mechanical algorithm for database search, In Proceeding of STOC'96, pp 212–219 ([quant-ph/9605043](https://arxiv.org/abs/quant-ph/9605043)).
 - [5] P. W. Shor, Polynomial-Time Algorithms for Prime Factorization and Discrete Logarithms on a Quantum Computer, *SIAM J. Sci. Statist. Comput.* **26**, 1484 (1997).
 - [6] A. Ambainis, Quantum Walks and their Algorithmic Applications, *Int. J. Quantum Inform.* **01**, 507 (2003).
 - [7] M. A. Nielsen and I. L. Chuang, Quantum Computation and Quantum Information, Cambridge University Press (2000).
 - [8] M. M. Wilde, Quantum Information Theory, Cambridge University Press (2013).
 - [9] M. D. Barrett, J. Chiaverini, T. Schaetz, J. Britton, W. M. Itano, J. D. Jost, E. Knill, C. Langer, D. Leibfried, R. Ozeri, and D. J. Wineland, Deterministic quantum teleportation of atomic qubits, *Nature* **429**, 737 (6993).
 - [10] J. T. Barreiro, T.-C. Wei, and P. G. Kwiat, Beating the channel capacity limit for linear photonic superdense coding, *Nature Physics* **4**, 282 (2008).
 - [11] A. S. Holevo, Bounds for the quantity of information transmitted by a quantum communication channel, *Problems of Information Transmission* **9**, 177 (1973).
 - [12] P. E. Frenkel and M. Weiner, Classical Information Storage in an n-Level Quantum System, *Commun. Math. Phys.* **340**, 563 (2015).
 - [13] S. Wiesner, Conjugate coding, *SIGACT News* **15**, 78 (1983).
 - [14] A. Ambainis, A. Nayak, A. Ta-Shama, U. Vazirani, Dense Quantum Coding and a Lower Bound for 1-Way Quantum Automata, *Proceedings of 31st ACM Symposium on Theory of Computing*, pp. 376–383, 1999.
 - [15] A. Ambainis, A. Nayak, A. Ta-Shama, and U. Vazirani, Dense Quantum Coding and Quantum Finite Automata, *Journal of the ACM* **49**, 496 (2002).
 - [16] B. Schumacher, Quantum Mechanics: The Physics of the Microscopic World, <http://www.thegreatcourses.com/courses/quantum-mechanics-the-physics-of-the-microscopic-world.html>.
 - [17] A. Tavakoli, A. Hameedi, B. Marques, and M. Bourennane, Quantum Random Access Codes Using Single d -Level Systems, *Phys. Rev. Lett.* **114**, 170502 (2015).
 - [18] A. Ambainis, D. Kravchenko, and A. Rai, Optimal Classical Random Access Codes Using Single d -level Systems, [arXiv:1510.03045](https://arxiv.org/abs/1510.03045).
 - [19] A. Nayak, Optimal Lower Bounds for Quantum Automata and Random Access Codes, *Proceedings of the 40th IEEE Symposium on Foundations of Computer Science (FOCS'99)*, pp. 369–376, 1999 ([e-print](https://arxiv.org/abs/quant-ph/9904017)).
 - [20] M. Hayashi, K. Iwama, H. Nishimura, R. Raymond, and S. Yamashita, $(4,1)$ -Quantum random access coding does

- not exist—one qubit is not enough to recover one of four bits, *New J. Phys.* **8**, 129 (2006).
- [21] A. Ambainis, D. Leung, L. Mancinska, and M. Ozols, Quantum Random Access Codes with Shared Randomness, [arXiv:0810.2937](#).
 - [22] E. F. Galvao, Ph.D. thesis, University of Oxford, 2002.
 - [23] Hartmut Klauck, Lower bounds for quantum communication complexity, Proceedings of the 42nd IEEE Symposium on Foundations of Computer Science (FOCS'01), pp. 288, 2001, [arXiv:quant-ph/0106160v3](#).
 - [24] Scott Aaronson, Limitations of Quantum Advice and One-Way Communication, Proceedings of the 19th Annual IEEE Conference on Computational Complexity (CCC'04), pp. 320–332, 2004. [arXiv:quant-ph/0402095v4](#).
 - [25] M. Hayashi, K. Iwama, H. Nishimura, R. Raymond, S. Yamashita, Quantum Network Coding, [arXiv:quant-ph/0601088](#).
 - [26] I. Kerenidis and R. de Wolf, Exponential Lower Bound for 2-Query Locally Decodable Codes via a Quantum Argument, *J. Comput. Syst. Sci.*, vol. 69, 3, pp. 395–420, 2004, [arXiv:quant-ph/0208062v2](#).
 - [27] S. Wehner and R. de Wolf, Improved Lower Bounds for Locally Decodable Codes and Private Information Retrieval, Automata, Languages and Programming, pp. 1424–1436, 2005, [arXiv:quant-ph/0403140v2](#).
 - [28] Scott Aaronson, The Learnability of Quantum States, *Proc. Roy. Soc. London Ser. A*, vol. 463, no. 2088, pp. 3089–3114, 2007, [arXiv:quant-ph/0608142v3](#).
 - [29] H.-W. Li, Z.-Q. Yin, Y.-C. Wu, X.-B. Zou, S. Wang, W. Chen, G.-C. Guo, and Z.-F. Han, Semi-device-independent random-number expansion without entanglement, *Phys. Rev. A* **84**, 034301 (2011).
 - [30] M. Pawłowski and N. Brunner, Semi-device-independent security of one-way quantum key distribution, *Phys. Rev. A* **84**, 010302(R) (2011).
 - [31] R. W. Spekkens, D. H. Buzacott, A. J. Keehn, B. Toner, and G. J. Pryde, Preparation Contextuality Powers Parity-Oblivious Multiplexing, *Phys. Rev. Lett.* **102**, 010401 (2009).
 - [32] M. Banik, S. S. Bhattacharya, A. Mukherjee, A. Roy, A. Ambainis, and A. Rai, Limited preparation contextuality in quantum theory and its relation to the Cirel'son bound, *Phys. Rev. A* **92**, 030103(R) (2015).
 - [33] A. Ambainis, M. Banik, A. Chaturvedi, D. Kravchenko, and A. Rai, Parity Oblivious d-Level Random Access Codes and Class of Noncontextuality Inequalities, [arXiv:1607.05490](#).